

Praesto® Q

**Agarose Highly Cross Linked
Strong Anion Exchanger**

Praesto Q is an agarose-based strong anion exchange resin designed for purification of different biomolecules, including proteins, peptides and oligonucleotides.

It is available in three separate particle sizes - 45 µm, 65 µm and 90 µm - making it the ideal choice for high resolution, intermediate and capture steps.

[Praesto Ion Exchange Chromatography Resins - FAQs](#)

GÓWNE ZASTOSOWANIA

- Protein purification (20-500 kDa)
- MAb Purification

ZALETY

- High dynamic binding capacity
- Enhanced pressure/flow performance
- High resolution/selectivity
- Chemical and physical stability
- Secure, validated supply and regulatory support

ZGODNO Z REGULACJAMI

- Manufactured under cGMP conditions

DOSTPNO OPAKOWA

- Bulk Resin
- Production-Scale OPUS® Columns
- OPUS® Robocolumns®
- OPUS® MiniChrom Columns
- HT Columns

PODSTAWOWE WACIWOCI FIZYCZNE I CHEMICZNE:

struktura polimeru	Highly cross linked agarose
Appearance	Spherical beads
grupa funkcyjna	Quaternary amine
Chemical stability	All commonly used aqueous buffers. 1M NaOH, 8M urea, 6M guanidine hydrochloride, 30% isopropanol and 70% ethanol
Avoid	Oxidising agents, anionic detergents
Ionic capacity - resin	0.14 - 0.18 mmol/ml
Ionic capacity - medium	0.14 - 0.18 mmol Cl ⁻ /ml
Particle Size - µm	45, 65, 90 µm
Dynamic Binding Capacity (min.) - 6 minutes residence time	70 BSA/ml
Pressure/flow (min.) - at 3 bar in a 2.6 x 20 cm column (pressure-packed at 4 bar)	200 cm/h
pH stability, CIP (short term)	2 - 14
pH stability, working range	3 - 13

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.



Americas
T +1 610 668 9090
F +1 610 668 8139
americas@purolite.com

**EMEA(Europa, Środkowy
Wschód i Afryka)**
T +44 1443 229334
F +44 1443 227073
europe@purolite.com

Asia Pacific
T +86 571 876 31382
F +86 571 876 31385
asiapacific@purolite.com

FSU
T +7 495 363 5056
F +7 495 564 8121
fsu@purolite.com