PRODUCT DATA SHEET

Purolite™ MB400IND

聚苯乙烯 凝胶, 混床树脂, 氢型, 氢氧型, 含指示剂

主要应用

- 脱盐 - 混床

产品优势

- 染色阴离子指示失效

适用系统

- 顺流再生系统
- 逆流再生系统
- 混床
- 工作混床

包装样式

- 1 CF 编织袋
- 25L 阀口袋
- 5 CF 纤维板桶

典型物理和化学参数

外观	球状颗粒	
粒径分布	300 - 1200 µm	
< 300 µm (最大)	1 %	
均一系数（最大）	1.7	
包装密度（大约）	705 - 740 g/L (44.1 - 46.2 lb/ft³)	
温度限制，不可再生床	100 °C (212.0 °F)	
温度限制，可再生床	60 °C (140.0 °F)	
组分名称	凝胶强酸阳树脂	凝胶I型强碱阴树脂
聚合物骨架	凝胶型聚苯乙烯二乙烯苯交联	凝胶型聚苯乙烯二乙烯苯交联
官能团	磺酸	季铵I型
离子型态	H^+	OH^-
阳离子/阴离子体积比	40 %	60 %

2026 Purolite
All rights reserved.

Ecolab is a global developer, manufacturer, and supplier of Purolite™ Resins including ion exchange, catalyst adsorbent and advanced polymers that make the world cleaner and healthier.

www.puroliteresins.com

We're ready to solve your process challenges.

For further information on products and services, visit www.puroliteresins.com or complete a Contact Us form via PuroliteResins.com/contact-us or use the QR code.

Contact Us Form:

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

2026 Purolite
All rights reserved.